

PRODUCT DESCRIPTION

Open Cell polyethylene backing rod for use in conjunction with Tremco sealants and membranes.

USAGE/PURPOSE

Tremco's Open Cell Backing Rod is designed to be used in conjunction with Tremco's sealants. It provides a highly durable bond-breaker to prevent 3-sided adhesion, which would otherwise reduce the sealant's functional elasticity.

Open Cell Backing Rod can be used for horizontal joints, but is ideal for vertical joints, commonly found in pre-cast panel butt joints, as well as around window/door perimeters, as it promotes quicker drying of the applied sealant when compared to Closed Cell Backing Rod. For more information on Tremco's backing rod selection guide, please visit www.tremco.com.au/technicalresources/technicalbulletins.

PACKAGING

- ❑ 10mm (W) x 210m (L)
- ❑ 16mm (W) x 150m (L)
- ❑ 22mm (W) x 100m (L)
- ❑ 29mm (W) x 60m (L)
- ❑ 38mm (W) x 60m (L)

COLOUR

Orange

SHELF LIFE

Unlimited.

STORAGE

Store in a dry cool place in an upright position in original, undamaged packaging.

LIMITATIONS

It is recommended that the backing rod is not installed in submerged or damp horizontal conditions, as the nature of the open cell will allow water to rise and potentially displace the sealant during cure.



HEALTH & SAFETY PRECAUTIONS

The Safety Data Sheet (SDS) must be read and understood prior to use.

TECHNICAL SERVICE

TREMCO has a team of Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

TREMCO products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with TREMCO written instructions and (b) in any application recommended by TREMCO, but which is proved to be defective, will be replaced free of charge.

Any information provided by TREMCO in this document in relation to TREMCO's goods or their use is given in good faith and is believed by TREMCO to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. TREMCO makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.